### > NSF Special Section inside: Building Water Health

October 2016 Vol. 22, Num. 10

M Engineer The must-read resource for engineering excellence

2016 ASPE Conference and Expo preview

e

Ballanco: Major code change coming up for debate.

www.pmengineer.com

# Making its mark

ASPE's Young Professionals group leads the next generation.

SCAN WITH YOUR SMARTPHONE TO ACCESS PMENGINEER.COM.



ASPE Young Professionals Liaison Cory Powers in Milwaukee.







#### **Toilet for kids**

The high-efficiency Elementary Toilet, which uses 1.28 gpf, is easy for kids to use. It includes several safety features such as a slow-closing seat to protect kids' fingers and a cover lock that prevents kids from playing with the tank trim. It is 24" to the top of the tank with a rim height of 11 1/4". This rim height meets ASME's juvenile height standards, as well as TAS standards for 5 to 8 year olds. The toilet joins Mansfield's extensive line of "green" toilets and urinals. **Mansfield Plumbing. www.mansfieldplumbing.com** 

#### **Convenient access inspection port**

Weil-McLain's Aqua PLUS line of indirect-fired water heaters feature high-output stainless-steel heat exchangers that deliver great firsthour ratings and recovery. The units' compact size allows for easy installation in low-ceiling basements or storage rooms, and thermostat connections already are installed for quick wiring. Other features include a magnesium anode rod for corrosion resistance and a large inspection port to provide convenient access for tank cleaning and inspection. Built with durability and longevity in mind, these AHRI-certified units are available in five sizes to suit any application. **Weil-McLain. www.weil-mclain.com** 





## Cascade multiple units without an external control box

Navien's NPE-S series condensing tankless water heaters feature an efficiency of 0.99EF. The models supply maximum inputs from 150,000 to 199,900 Btu/hr., and efficient outputs from 148,500 to 197,900 Btu/hr. Maximum flow rates are from 8.4 gpm to 11.1 gpm. Other features include: 1/2" gas pipe capability up to 24', 2" PVC venting up to 60', dual stainlesssteel heat exchangers, field gas convertibility and cascade capability up to 16 units without an external control box. **Navien. www.navien.com** 

#### Strong, flexible, pure

Legend's HyperPure polyethylene raised-temperature tubing for potable water systems is strong, flexible and pure, the company notes. This flexible plastic hot and cold potable water tube is 100% recyclable because it is made using a bimodal resin which does not need to be cross-linked. It meets and exceeds the rigorous potable water standards. It is: easy-to-use, compatible with most fitting systems, tasteless and odorless requiring no flushing, available in 1/4" to 2" coils and 20' lengths. **Legend**. **www.legendvalve.com** 





#### Space-savvy toilet

ICERA's Malibu II is a 1.28-gpf, high-efficiency, space-savvy toilet that combines style with high performance standards. It is available in either a one- or two-piece model. It features: a compact-elongated bowl, fully skirted profile, a soft-close and quick-release seat, ADA-compliant chair-height bowl, an oversize 2 1/8" trapway, 3" flush valve, EcoQuattro flushing system, precision rim jets, and a MicroGlaze non-staining, anti-microbial finish. Crafted of vitreous china, it is available in white and Balsa, and includes a polished-chrome solid-metal trip lever and color-matched plastic floor bolt covers. Other metallic finishes are available. **ICERA. www.icerausa.com**