The Western Authority on Plumbing, HVAC and Piping

ALSO:

CALIFORNIA PART OF THE DROUGHT IS OVER(?) WHOLE-HOUSE FILTRATION WESTERN WATER QUALITY ROUNDUP

LIMIT

1000

ROAD

SUBJECT TO FLOODING

DO NOT

WATER

REEVES JOURNAL

March 2017, Vol 97, No 3 www.reevesjournal.com

A bop PUBLICATIO



MIX-AND-MATCH BATH FIXTURES

Isenberg's Series 145 includes 21 coordinating pieces. Users can choose from a single-hole basin faucet, a deck-mounted Roman faucet, or a freestanding tub filler. Options include a variety of configurations for sinks and tubs, as well as thermostatic shower valves and diverters. There are coordinating accessory pieces to choose from, such as towel bars, robe hooks and paper holders. Hidden aerators are featured in the 8" widespread and Roman tub spouts to deliver a smooth, splash-free stream of water and promote eco-friendly water conservation. Made with solid brass construction, the series is available in chrome, polished brass, and polished nickel.

ISENBERG | www.isenbergfaucets.com RS# 204 at www.ReevesJournal.com/adindex



MIMIC NATURAL RAIN

Kohler's Real Rain relies on gravity rather than the typical pressurized spray to shape the water, using 775 concave nozzles to start the storm off slowly and then build. The rates at which the drops fall is varying and random. It has a 6" dry area when not in deluge mode that keeps the rain away from the face. The ceiling-mount panel measures 19" x 19". It flows at 2 gpm and complies with CALGreen requirements. Available finishes include Polished Chrome, Vibrant Polished and Brushed Nickel, Matte Black, Vibrant Titanium, Vibrant Brushed Bronze and Oil-Rubbed Bronze.

KOHLER | www.us.kohler.com RS# 207 at www.ReevesJournal.com/adindex



PE-RT & PEX CONNECTION SYSTEM

Legend's SmartClick PE-RT and PEX Connection System is five times faster to install than other fitting systems. In seconds you have a permanent connection without using any tools. Insert the tube into the connector until you hear the click. The audible click tells you that the spring steel clamp inside the connector has been actuated and you have a permanent connection. It is for use in potable water plumbing systems utilizing PE-RT (ASTM F 2769) or PEX (ASTM 876/877). The fittings are third party certified by IAPMO and are ANSI/NSF 61, ANSI/NSF 14 and ASSE 1061 compliant.

LEGEND | www.legendvalve.com RS# 206 at www.ReevesJournal.com/adindex

DUAL CONTROL SHOWER PANEL

Lenova's Thermostatic Shower Panel is an all-inclusive shower system that offers a rain shower top, multiple body sprayers and a handheld shower. The single handle design offers high pressure resistance and dual control over both water flow and temperature. The system provides stability over water temperature, maintaining temperatures within one degree even when the rain shower and body sprayers are used simultaneously. As an added safety measure, its handle stays cool even when the water is hot. Available in a stainless-steel finish, it measures 50" x 8" with a 19" shower head depth.

LENOVA | www.LenovaSinks.com. RS# 205 at www.ReevesJournal.com/adindex



