

# SOUTHERN PHC



PLUMBING • HEATING • COOLING  
1946 - serving the industry for over 70 years

February | March 2018

## AHR Expo Highlights

page 20

## Highlights from KBIS/IBS

page 24

## Focus on Pipes, Valves & Fittings

page 6

## Executive Profile: Jason Fleming Noritz

page 33

PERMIT 43  
MACON, GA  
PAID  
US POSTAGE  
PRESRT STD

AUTO-3-DIGIT 342

Change Service Requested

Southern Trade Publications  
P.O. Box 7344  
Greensboro, NC 27417



southernphc.com

## Victoria + Albert Introduces New Trivento Bateau Bathtub

[vandabaths.com](http://vandabaths.com)

Victoria + Albert have unveiled the Trivento, a modern reinvention of the classic bateau, or "boat bath," bathtub.

Featuring a fine rim and a deep, double-ended bathing well, Trivento measures 22-7/8" high by 27-7/8" wide and 65" long, Trivento works with Victoria + Albert's Kit 40 Intelli-waste bath drain and is available in seven external finishes, including Gloss White, Gloss Black, Matte White, Matte Black, Anthracite, Stone Grey, and Light Grey.



## RSES Adds Four More HVACR Training Products to Online Store

[rses.org/store](http://rses.org/store)

RSES has added four additional HVACR training books to its online store: *Carbon Monoxide: A Clear and Present Danger*, the *System Performance* manual, *Combustion Analysis & Fuel Efficiency* and *Solar Hot Water Fundamentals*.

Sample sections of each manual are available in the Table of Contents tab in the description section at the online store. RSES Members will need to login to the website first in order to receive the appropriate member discount.



## Taco's Multi-Purpose Tanks Built for Broad Application

[taco.com](http://taco.com)

Taco Comfort Solutions' line of chilled and hot water multi-purpose tanks provides the options and durability needed for a broad range of hydronic applications.

The multi-purpose tanks (MPT), which range in standard sizes from 50 to 1,050 gallons, are built to last with ANSI flanges and are ASME rated for 125 and 150 psi working pressures and a maximum operating temperature of 240°F. Flanges are available from 2-inch through 10-inch.